



2920 Series



2920AL Series



2516 Series

Liquidtight Flexible Cord and Cable Connectors

Application

- A liquidtight connector to connect flexible cord or cable to an enclosure and provide adequate strain relief

Features

- Liquidtight connection with enclosure is assured by:
 - (A) Taper threaded hub on 2520 series for female hub application
 - (B) Using sealing ring series 5262 with 2520 series for knockout application
 - (C) Captivated sealing 'O' ring on 2631 series
 - (D) Neoprene bushing makes liquidtight installation; applies pressure against cable the full length of bushing
 - (E) Thermoplastic or stainless steel retaining ring
 - (1) Will not abrade cord/cable jacket
 - (2) Reduces installing torque effort
- U.L. Listed liquidtight, strain relief and as an outlet bushing; CSA certified watertight

Standard Material

Gland, Body ..	Steel/Malleable Iron/Zinc Die Cast
Retaining Ring	Thermoplastic/ Stainless Steel
Bushing	Neoprene
'O' Ring	Buna N

Standard Finish

Electro Zinc Plated & Chromate Coated

Range

2520 Series, straight	125" outside diameter to 3.200" outside diameter Cord or Cable
2200 Series, 45°	125" outside diameter to 1.485" outside diameter Cord or Cable
2267 Series, 90°	125" outside diameter to 1.875" outside diameter Cord or Cable
Cord/Cable Type	S, SO, SV, ST, STO, SJ, SJO, SJT, SJTO, SVO & SVT

Listed/Certified by:

U.L.(U.L. File No. E-13938)
 CSALR-589, LR-4484

Conforms to:

U.L. 514
 CSA 22.2 No. 18
 ANSI C33.84, NFPA 70-1978 (ANSI)

