




T&B Conduit Fittings

Liquidtight Flexible Metal Conduit Fittings



Steel, malleable iron, or aluminum tapered hub threads. With safe-edge ground thru 4" cone and double bevel sealing ring (through 2").



Malleable iron, tapered hub threads. With safe-edge ground cone and double bevel sealing ring (through 2").

Liquidtight Flexible Metal Conduit Fittings For Control and Power Cable Applications

Cat. No.	Hub Size	Conduit Size	Dimensions (in.)		
			A	B	C
5229*	1/4"	1/4	27/32	1-3/8	15/32
5330*	3/8"	5/16	63/64	1-3/8	15/32

* U.L. and CSA not applicable.

Straight Fittings



Insulated	Cat. No.		Conduit Size	Dimensions (in.)		
	Aluminum*	Noninsulated		A	B	C
5331**♦	5231AL	5231	3/8	1-5/32	1-1/2	9/16
5332♦	5232AL	5232	1/2	1-3/8	1-9/16	9/16
5333♦	5233AL	5233	3/4	1-21/32	1-5/8	9/16
5334♦	5234AL	5234	1	1-7/8	2-1/16	3/4
5335+	5235AL	5235	1-1/4	29/32	2-1/2	13/16
5336+	5236AL	5236	1-1/2	2-23/32	2-11/16	13/16
5337+	5237AL	5237	2	3-1/4	3-1/16	7/8
5338+	5238AL	5238	2-1/2	3-3/4	4-1/8	1
5339+	5239AL	5239	3	4-1/2	4-1/4	1
5340+	5240AL	5240	4	5-1/2	4-1/2	1-1/8
5385*+	—	5285*	5	8-3/4	7	1-7/8
5386*+	—	—	6	8-3/4	8-1/2	2

Suitable for hazardous locations use in CEC Rule 18-152 (6) Class I, Zone 2; CEC Rule J18-152 (6) Class I, Division 2; CEC Rule 18-202 (4) Class II, Division 1; CEC Rule 18-252 (4) Class II, Division 1

** 3/8" Conduit Fitting has 1/2" hub.

U.L. Listed liquidtight; and CSA Certified watertight.

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.

* Not CSA Certified.

♦ Steel

+ Malleable Iron

45° Angle Fittings*



Insulated	Cat. No.		Conduit Size	Dimensions (in.)		
	Noninsulated			A	B	C
5341**	5241		3/8	1-5/32	1-9/16	9/16
5342	5242		1/2	1-3/8	1-7/8	9/16
5343	5243		3/4	1-21/32	2-1/8	9/16
5344	5244		1	1-7/8	2-1/4	3/4
5345	5245		1-1/4	29/32	2-3/4	1-3/16
5346	5246		1-1/2	2-23/32	3-3/8	1-3/16
5347	5247		2	3-1/4	3-7/8	7/8
5348	5248		2-1/2	3-3/4	4-1/4	1
5349	5249		3	4-1/2	4-1/4	1
5350	5250		4	5-1/2	4-5/8	1-1/8

* Suitable for hazardous locations use CEC Rule 18-152 (6) Class I, Zone 2; CEC Rule J18-152 (6) Class I, Division 2; CEC Rule 18-202 (4) Class II, Division 1; CEC Rule 18-252 (4) Class II, Division 1

** 3/8" Conduit Fitting has 1/2" hub.

U.L. Listed liquidtight; and CSA Certified watertight.

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.

For Wiremesh Grips refer to page 80.